

HYUNDAI (EU) H 300 TQ (NL) H 300 2.4 MPI (2007-2009)

**ENGINE**

Capacity: 4,3 liter, Capacity: 4,4 liter (+ oil cooler)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 20W-50	Multifleet SHPD 20W-50	

Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Duranza LSP 5W-30	Asyntho 5W-30

Change every 15000 km/ 12 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 20W-50	Multifleet SHPD 20W-50	

Change every 7500 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Duranza LSP 5W-30	Asyntho 5W-30

*Change every 7500 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,8-2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 24 months/ 30000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 30000 km/ 24 months, change every 90000 km

HYUNDAI (EU) H 300 TQ (NL) H 300 2.4 MPI (2007-2009)


TRANSMISSION AUTOMATIC 4/1

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	ATF Dexron II-D	

Check every 15000 km/ 12 months, change every 90000 km/ 72 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	ATF Dexron II-D	

Check every 15000 km/ 12 months, change every 40000 km

TRANSMISSION MANUAL 5/1

Capacity: 1,95 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Check every 15000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Check every 15000 km/ 12 months, change every 100000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months

HYUNDAI (EU) H 300 TQ (NL) H 300 2.4 MPI (2007-2009)



POWER STEERING

Capacity: 0,9-1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 15000 km/ 12 months

COOLING SYSTEM

Capacity: 7,1-10,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

Change every 40000 km/ 24 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

Change every 100000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.