

ISUZU D-MAX / RODEO D-MAX / RODEO 3.0 TD AWD (2006-2012)

**ENGINE 4JJ1-TC**

Capacity: 8 liter (Dry fill), Capacity: 6,9 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Change every 10000 km/ 12 months***DIFFERENTIAL FRONT**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140*Check every 20000 km/ 24 months, change every 40000 km/ 48 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 20000 km/ 24 months, change every 40000 km/ 48 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Gearlube RPC 75W-80*Check every 20000 km/ 24 months, change every 40000 km/ 48 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 1081*Check every 20000 km/ 24 months, change every 40000 km/ 48 months*

ISUZU D-MAX / RODEO D-MAX / RODEO 3.0 TD AWD (2006-2012)

**DIFFERENTIAL REAR**

Capacity: 1,4 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 20000 km/ 24 months, change every 40000 km/ 48 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 20000 km/ 24 months, change every 40000 km/ 48 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Gearlube RPC 75W-80

Check every 20000 km/ 24 months, change every 40000 km/ 48 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Check every 20000 km/ 24 months, change every 40000 km/ 48 months

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	Gearlube LS 80W-90	Unigear LS GL-3/GL-5 85W-140

Check every 20000 km/ 24 months, change every 40000 km/ 48 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
SP Gear LS 1015		

Check every 20000 km/ 24 months, change every 40000 km/ 48 months

ISUZU D-MAX / RODEO D-MAX / RODEO 3.0 TD AWD (2006-2012)

**TRANSFERBOX**

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 10W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 20000 km/ 24 months, change every 40000 km/ 48 months

TRANSMISSION AUTOMATIC AW30-40 LE 4/1

Capacity: 8,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 40000 km/ 48 months

TRANSMISSION MANUAL 5/1

Capacity: 2,95 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 20000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Change every 20000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 24 months

ISUZU D-MAX / RODEO D-MAX / RODEO 3.0 TD AWD (2006-2012)



HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 24 months

POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 100000 km/ 60 months

COOLING SYSTEM

Capacity: 8,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 100000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.