

IVECO DAILY 29 DAILY 29 L 9 (1999-2002)

**ENGINE 8140.63.4..**

Capacity: 6,3 liter, Capacity: 6,9 liter (Dry fill), Filter capacity: 1,1 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Multifleet SCD 40 | Multifleet SCD 30 | |

Change every 10000 km/ 200 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 10000 km/ 200 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | | |
|------------------------------|--|--|
| Multifleet SCD 20W-20 | | |

Change every 10000 km/ 200 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Multifleet SCD 10W | | |

*Change every 10000 km/ 200 hours***DIFFERENTIAL REAR 4517**

Capacity: 1,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

*Change every 90000 km/ 1800 hours***TRANSMISSION MANUAL ZF 5S-200 5/1**

Capacity: 2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|-----------------------------|--|
| SP Gear 5015 | Syngear MT/LD 75W-80 | |

Change every 90000 km/ 1800 hours

IVECO DAILY 29 DAILY 29 L 9 (1999-2002)**HYDRAULIC BRAKE SYSTEM**

Capacity: 1,1 liter

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

*Change every 24 months***POWER STEERING ZF 8090**

Capacity: 1,4 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |

GREASE POINTS/NIPPLES BEARINGS

| USE | | CLIMATE |
|--------------------------|-------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Labora Grease | Multi Purpose Grease 3 | |

GREASE POINTS/NIPPLES OTHERS

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM

Capacity: 9 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.