IVECO DAILY 40 DAILY 40 C 9(1999-2002)



ENGINE 8140.63.4 Capacity: 6,3 liter, Filter capacity: 1,1 l	iter		
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 40	Multifleet SCD 30		
Change every 10000 km/ 200 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Change every 10000 km/ 200 hours			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 20W-20			
Change every 10000 km/ 200 hours			
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 10W			
Change every 10000 km/ 200 hours			

	1	1
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
DIFFERENTIAL REAR 4517 Capacity: 1,8 liter		

Change every 90000 km/ 1800 hours

TRANSMISSION MANUAL ZF 5S-200 5/ Capacity: 2 liter	1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear MT/LD 75W-80	
<u> </u>	•	

Change every 90000 km/ 1800 hours



HYDRAULIC BRAKE SYSTEM Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

POWER STEERING ZF 8090 Capacity: 1,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

GREASE POINTS/NIPPLES BEARINGS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Labora Grease	Multi Purpose Grease 3		

GREASE POINTS/NIPPLES OTHERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 36 months		·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.