

## IVECO DAILY 50 DAILY 50 C 17 EEV (2009-2011)

**ENGINE F1C**

| USE                       |                          | CLIMATE                  |
|---------------------------|--------------------------|--------------------------|
| Normal                    |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Presteza MSP 5W-30</b> | <b>Avanza MSP+ 5W-30</b> | <b>Avanza RPC 5W-30</b>  |

*Change every 40000 km/ 800 hours*

**DIFFERENTIAL REAR**

| USE                          |                                     | CLIMATE  |
|------------------------------|-------------------------------------|----------|
| Normal                       |                                     | Moderate |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |          |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |          |

*Change every 80000 km/ 24 months/ 1600 hours*

| USE                         |                                    | CLIMATE |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Arctic  |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

*Change every 80000 km/ 24 months/ 1600 hours*

**TRANSMISSION AUTOMATED ZF 6AS-400 6/1**

Capacity: 2,2 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Syngear MT/LD 75W-80</b> |  |          |

*Change every 120000 km/ 2400 hours*

**TRANSMISSION MANUAL Iveco 2840.6 6/1**

| USE                      |                             | CLIMATE  |
|--------------------------|-----------------------------|----------|
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| <b>SP Gear 5015</b>      | <b>Syngear MT/LD 75W-80</b> |          |

*Change every 120000 km/ 2400 hours*

# IVECO DAILY 50 DAILY 50 C 17 EEV (2009-2011)



## HYDRAULIC BRAKE SYSTEM

Capacity: 1,1 liter

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Check every 40000 km/ 800 hours, change every 24 months

## HYDRAULIC CLUTCH SYSTEM

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

## POWER STEERING

Capacity: 1,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

Check every 40000 km/ 800 hours

## COOLING SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 11</b>     |  |          |

Check every 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.