

IVECO DAILY 65 DAILY 65 C 17 (2011-2014)

**ENGINE F1CE3481C**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 40000 km/ 24 months/ 800 hours

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 20000 km/ 12 months

USE	CLIMATE
Fuel sulfur level >0,5%	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 20000 km

DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 80000 km/ 24 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 80000 km/ 24 months

TRANSMISSION AUTOMATED ZF 6AS-400 6/1

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 120000 km/ 2400 hours/ 36 months

IVECO DAILY 65 DAILY 65 C 17 (2011-2014)



TRANSMISSION MANUAL FPT 2840.6 6/1

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear MT/LD 75W-80	

Change every 120000 km/ 2400 hours/ 36 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 40000 km/ 800 hours, change every 24 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	

COOLING SYSTEM BLUE FLUID

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 12 months, change every 36 months

IVECO DAILY 65 DAILY 65 C 17 (2011-2014)**COOLING SYSTEM YELLOW FLUID**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.