

IVECO DAILY 65 DAILY 65 C 17 (2014-2016)

**ENGINE F1CFL411**

Capacity: 6,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30

Change every 40000 km/ 24 months/ 800 hours

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30

Change every 20000 km/ 400 hours/ 12 months

USE	CLIMATE
Fuel sulfur level >0,5%	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30

Change every 20000 km/ 400 hours/ 12 months

DIFFERENTIAL REAR (4x2) 450517/2

Capacity: 3,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 80000 km/ 24 months/ 1600 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 80000 km/ 24 months/ 1600 hours

TRANSMISSION AUTOMATED ZF 6AS-400A OD 6/1

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear MT/LD 75W-80	

Change every 120000 km/ 2400 hours/ 36 months

IVECO DAILY 65 DAILY 65 C 17 (2014-2016)

TRANSMISSION AUTOMATIC ZF 8HP (HI-MATIC) 8/1
Capacity: 9,5 liter (Dry fill), Capacity: 3,5-5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034*Change every 200000 km/ 4000 hours*

TRANSMISSION MANUAL FPT 2840.6 OD 6/1
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80*Change every 120000 km/ 2400 hours/ 36 months*

HYDRAULIC BRAKE SYSTEM
Capacity: 1,11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 40000 km/ 12 months/ 800 hours, change every 24 months*

POWER STEERING
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D**GREASE POINTS/NIPPLES WHEEL BEARINGS**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Multi Purpose Grease 3

IVECO DAILY 65 DAILY 65 C 17 (2014-2016)**COOLING SYSTEM**

Capacity: 16 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12****PRODUCT RECOMMENDATION 3****Coolant -38 Organic NF***Check every 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.