PRODUCT RECOMMENDATION

IVECO DAILY 70 DAILY 70 C 21 (2014-2016)

ENGINE F1CFL411
Capacity: 6,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Duranza MSP 0W-30	**Presteza MSP 0W-30**	**Avanza MSP 0W-30**

Change every 40000 km/ 24 months/ 800 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Duranza MSP 0W-30	**Presteza MSP 0W-30**	**Avanza MSP 0W-30**

Change every 20000 km/ 400 hours/ 12 months

USE		CLIMATE
Fuel sulfur level >0,5%		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Duranza MSP 0W-30	**Presteza MSP 0W-30**	**Avanza MSP 0W-30**

Change every 20000 km/ 400 hours/ 12 months

DIFFERENTIAL REAR (4x2) 450517/2
Capacity: 3,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

Change every 80000 km/ 24 months/ 1600 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 80000 km/ 24 months/ 1600 hours

TRANSMISSION AUTOMATIC ZF 8HP (HI-MATIC) 8/1
Capacity: 9,5 liter (Dry fill), Capacity: 3,5-5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2034		

Change every 200000 km/ 4000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

IVECO DAILY 70 DAILY 70 C 21 (2014-2016)

TRANSMISSION MANUAL FPT 2850.6 DOD 6/1
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	**Syngear MT/LD 75W-80**	

Change every 120000 km/ 2400 hours/ 36 months

HYDRAULIC BRAKE SYSTEM
Capacity: 1,11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 40000 km/ 12 months/ 800 hours, change every 24 months

POWER STEERING
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	**Multi Purpose Grease 3**	

COOLING SYSTEM
Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367