

# KIA (EU) CARNIVAL/SEDONA VQ

## CARNIVAL 3.5 V6 (2010-2014)



**ENGINE** Lambda II 3.5  
Capacity: 5,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>	<b>Bi-Turbo 20W-50</b>

*Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza ECO 5W-20</b>	<b>Presteza MSP 5W-30</b>	<b>Duranza LSP 5W-30</b>

*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>	<b>Bi-Turbo 20W-50</b>

*Change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza ECO 5W-20</b>	<b>Presteza MSP 5W-30</b>	<b>Duranza LSP 5W-30</b>

*Change every 7500 km/ 6 months*

**TRANSAXLE AUTOMATIC 5/1**  
Capacity: 7,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 15000 km/ 12 months, change every 90000 km/ 72 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 15000 km/ 12 months, change every 45000 km*

# KIA (EU) CARNIVAL/SEDONA VQ

## CARNIVAL 3.5 V6 (2010-2014)



### HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

### POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

Check every 15000 km/ 12 months

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

### COOLING SYSTEM

Capacity: 8,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Check every 30000 km/ 24 months, change every 210000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.