

KIA (EU) PREGIO/BESTA PREGIO 2.7 D (2005-2006)



ENGINE J2
Capacity: 6,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40

Change every 7500 km/ 6 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40

Change every 4000 km/ 6 months

DIFFERENTIAL REAR
Capacity: 1,3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 20000 km, change every 40000 km/ 24 months

DIFFERENTIAL REAR LIMITED SLIP
Capacity: 1,3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 20000 km, change every 40000 km/ 24 months

KIA (EU) PREGIO/BESTA PREGIO 2.7 D (2005-2006)


TRANSAXLE AUTOMATIC 4/1

Capacity: 6,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 20000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 20000 km/ 12 months, change every 40000 km*
TRANSMISSION MANUAL M5ZR1 5/1

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 20000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 20000 km/ 12 months, change every 100000 km*
HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

KIA (EU) PREGIO/BESTA PREGIO 2.7 D

(2005-2006)



POWER STEERING

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM

Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10000 km/ 6 months, change every 100000 km/ 60 months

AIRCONDITIONING COMPRESSOR

Capacity: 100 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.