## LDV LD100 LD100 CRD KOMBI (88 KW) (<3.5T GVW) (2005-2009)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	

Change every 20000 km/ 12 months

TRANSAXLE MANUAL Wia, HTX Capacity: 2,35 liter	K, PVH 5/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 20000 miles/ 12 mon	ths	
USE		CLIMATE
First change only		Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3

SP Gear 1011 Syngear TDL 75W-90 Syngear 75W-90

Change every 20000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 20000 miles/ 12 months, change every 24 months

POWER STEERING Capacity: 0,43 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 20000 miles/ 12 months	

## LDV LD100 LD100 CRD KOMBI (88 KW) (<3.5T GVW) (2005-2009)



COOLING SYSTEM Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 20000 miles/ 12 month	s, change every 100000 miles/24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.