

PRODUCT RECOMMENDATION

LDV MAXUS MAXUS KOMBI (88 KW) (<3.5T GVW) (2005-2009)



ENGINE VM R2516L
Capacity: 6,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|-----------------------------|--|
| Emperol 10W-40 | Synfleet SHPD 10W-40 | |

Change every 20000 km/ 12 months

TRANSAXLE MANUAL Wia, HTX, PVH 5/1
Capacity: 2,35 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

Check every 20000 miles/ 12 months

| USE | CLIMATE |
|-------------------|----------|
| First change only | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

Change every 20000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|---------------------------|--|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Check every 20000 miles/ 12 months, change every 24 months

POWER STEERING
Capacity: 0,43 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| ATF Dexron II-D | | |

Check every 20000 miles/ 12 months

LDV MAXUS MAXUS KOMBI (88 KW) (<3.5T GVW) (2005-2009)



COOLING SYSTEM

Capacity: 11 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 20000 miles/ 12 months, change every 100000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.