

MERCEDES-BENZ (EU) TRANSPORTER 510

(667) (1982-1995)



ENGINE M102
Capacity: 4,5 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 10000 km/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40

Change every 10000 km/ 12 months

DIFFERENTIAL REAR
Capacity: 1,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 80W-90

Check every 10000 km, change every 40000 km

POWER TAKE OFF
Capacity: 0,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

ATF-A

Check every 20000 km, change every 60000 km

TRANSMISSION AUTOMATIC 4/1
Capacity: 6,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032

PRODUCT RECOMMENDATION 3

ATF Almirol

Check every 20000 km, change every 40000 km

MERCEDES-BENZ (EU) TRANSPORTER 510

(667) (1982-1995)


TRANSMISSION MANUAL GEARBOX NO. 711.110/571971 711.113/572187 -> 5/1

Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Syngear MT/LD 75W-80	Gearlube GL-4 80W	Gearlube GL-4 80W-90

Check every 20000 km, change every 60000 km

TRANSMISSION MANUAL UPTO GEARBOX NO. 711.109/571970 711.112/572186 5/1

Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 20000 km, change every 60000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,75 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 12 months

POWER STEERING

Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF Dexron II-D

GREASE POINTS/NIPPLES SLIDING JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 10000 km

MERCEDES-BENZ (EU) TRANSPORTER 510

(667) (1982-1995)



GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 10000 km

COOLING SYSTEM

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 36 months

STEERING BOX

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Check every 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.