

MERCEDES-BENZ (EU) VIANO 639 VIANO CDI 2.0 DPF (2007-2010)



ENGINE OM646 DE22
Capacity: 9 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 3

Presteza MSP 5W-30

DIFFERENTIAL REAR
Capacity: 1,3 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90*Change every 120 months*

TRANSMISSION AUTOMATIC 722.6xx 5/1
Capacity: 7,6 liter (Initial fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 120000 km*

USE

First change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 45000 km/ 24 months*

TRANSMISSION MANUAL 716.652 6/1
Capacity: 1,5 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 120 months*

MERCEDES-BENZ (EU) VIANO 639 VIANO CDI 2.0 DPF (2007-2010)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,8 liter, Capacity: 1 liter (Brake system + ESP)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 24 months*

POWER STEERING

Capacity: 0,8-1 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032

COOLING SYSTEM

Capacity: 8,6 liter, Capacity: 10,5 liter (Vito/Viano CDI type 639 + code H13/HZ7)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO*Change every 250000 km/ 180 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.