## MERCEDES-BENZ (EU) VITO 447 VITO 114 CDI (2014-2020)



ENGINE OM651.950 Capacity: 9 liter		
		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

### DIFFERENTIAL REAR

Capacity: 1,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION AUTOMATIC 722.9xx 7/1 Capacity: 9 liter (+ torque converter), Capacity: 10 liter (Dry fill), Capacity: 5,5 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 2094				
Change every 125000 km				
USE		CLIMATE		
Initial service		Moderate		

### PRODUCT RECOMMENDATION 1

#### SP Matic 2094

Change every 50000 km

TRANSMISSION MANUAL 711.680 6/1 Capacity: 2,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

Change every 200000 km/ 120 months

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid-S DOT 4			
Change every 24 months			

# MERCEDES-BENZ (EU) VITO 447 VITO 114 CDI (2014-2020)



COOLING SYSTEM Capacity: 10,4 liter, Capacity: 13,4 liter (with additional heater)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 12 EVO				
Change every 200000 $km/180$ months				

Change every 200000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.