MERCEDES-BENZ (EU) VITO 447 VITO 116 CDI (2014-2020)



| ENGINE OM651.950 Capacity: 9 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Flexible (on board maintenance system) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar SP LL-03 0W-30 | Helar SP LL-03 5W-30 | Presteza MSP 5W-30 |

DIFFERENTIAL REARCapacity: 1,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| TRANSMISSION AUTOMATIC 722.9xx 7/1 Capacity: 9 liter (+ torque converter), Capacity: 10 liter (Dry fill), Capacity: 5,5 liter (Service fill) | | | | |
|--|--|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| SP Matic 2094 | | | | |
| Change every 125000 km | | | | |
| USE | | CLIMATE | | |
| Initial service | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| SP Matic 2094 | | | | |
| Change every 50000 km | | | | |

| TRANSMISSION MANUAL 711.680 6/1 Capacity: 2,1 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Gear 5015 | |
| Change every 200000 km/ 180 months | · |

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.) | | | |
|--|----------|--|--|
| USE | CLIMATE | | |
| Normal | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| Drauliquid-S DOT 4 | | | |
| Change every 24 months | · | | |

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) VITO 447 VITO 116 CDI (2014-2020)



| COOLING SYSTEM Capacity: 10,4 liter, Capacity: 13,4 liter (with additional heater) | | | | |
|--|--|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Coolant SP 12 EVO | | | | |
| Change every 180 months | | | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.