

MERCEDES-BENZ (EU) VITO 639 VITO 115 CDI (2005-2010)



ENGINE OM646.984
Capacity: 9 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

DIFFERENTIAL REAR
Capacity: 1,3 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

Change every 120 months

TRANSMISSION AUTOMATIC 722.6xx 5/1
Capacity: 7,6 liter (Initial fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 120000 km

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 45000 km/ 24 months

TRANSMISSION MANUAL 716.637 6/1
Capacity: 1,2 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Change every 120 months

MERCEDES-BENZ (EU) VITO 639 VITO 115 CDI (2005-2010)


TRANSMISSION MANUAL 716.652 6/1

Capacity: 1,5 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 120 months*
HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,8 liter, Capacity: 1 liter (Brake system + ESP)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 24 months*
POWER STEERING

Capacity: 0,8-1 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032
COOLING SYSTEM

Capacity: 8,6 liter, Capacity: 10,5 liter (Vito/Viano CDI type 639 + code H13/HZ7)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO*Change every 250000 km/ 180 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.