

MERCEDES-BENZ (EU) VITO 639 VITO 122

CDI DPF (2010-2014)



ENGINE OM642 DE30
Capacity: 10 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 3

Presteza MSP 5W-30

DIFFERENTIAL REAR
Capacity: 1,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 1071

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90

Change every 300000 km/ 120 months

TRANSMISSION AUTOMATIC 722.6xx 5/1
Capacity: 7,1-7,8 liter (Dry fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 120000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0,8 liter, Capacity: 1 liter (Brake system + ESP)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

Change every 24 months

POWER STEERING

Capacity: 0,8-1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032

MERCEDES-BENZ (EU) VITO 639 VITO 122

CDI DPF (2010-2014)

**COOLING SYSTEM**

Capacity: 11 liter, Capacity: 14 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 300000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.