

MITSUBISHI (EU) L300 L300 2.5 TD (1996-2006)

**ENGINE 4D56**

Capacity: 5,5 liter, Capacity: 4,2 liter (Cabin/Chassis model), Filter capacity: 0,8 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 7500 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40*Change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 4000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40*Change every 4000 km***DIFFERENTIAL REAR (4x2)**

Capacity: 1,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 45000 km/ 36 months, change every 90000 km/ 72 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Check every 45000 km/ 36 months, change every 90000 km/ 72 months*

MITSUBISHI (EU) L300 L300 2.5 TD (1996-2006)



DIFFERENTIAL REAR LIMITED SLIP (4x2)

Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 30000 km/ 12 months, change every 45000 km/ 36 months

TRANSMISSION MANUAL 5/1

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear MT/LD 75W-80

Check every 15000 km/ 12 months, change every 75000 km/ 60 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months

POWER STEERING

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

MITSUBISHI (EU) L300 L300 2.5 TD (1996-2006)



COOLING SYSTEM

Capacity: 8,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.