

# NISSAN (EU) PATROL PATROL GR 2.8 TD

## 2WD Y60 (1988-1997)

**ENGINE**

Capacity: 6,4 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Asyntho 5W-30****PRODUCT RECOMMENDATION 2****Emperol 10W-40****PRODUCT RECOMMENDATION 3****Bi-Turbo 15W-40***Change every 5000 km/ 6 months***DIFFERENTIAL REAR H233B**

Capacity: 2,1 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 85W-140***Change every 40000 km/ 48 months***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****SP Gear 5015****PRODUCT RECOMMENDATION 3****Gearlube RPC 75W-80***Change every 40000 km/ 48 months***USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****SP Gear 1081***Change every 40000 km/ 48 months***DIFFERENTIAL REAR LIMITED SLIP (4x2)****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube Racing 75W-140**

# NISSAN (EU) PATROL PATROL GR 2.8 TD

## 2WD Y60 (1988-1997)


**DIFFERENTIAL REAR WITH DIFFERENTIAL LOCK (4x2)**

Capacity: 3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1  
**Gearlube GL-5 85W-140**

Change every 40000 km/ 48 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1  
**SP Gear 1011**

PRODUCT RECOMMENDATION 2  
**SP Gear 5015**

PRODUCT RECOMMENDATION 3  
**Gearlube RPC 75W-80**

Change every 40000 km/ 48 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1  
**SP Gear 1081**

Change every 40000 km/ 48 months

**TRANSMISSION MANUAL FS5R30A 5/1**

Capacity: 3,9 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1  
**Unigear LS GL-3/GL-5 85W-140**

Change every 40000 km/ 48 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1  
**SP Gear 1011**

PRODUCT RECOMMENDATION 2  
**SP Gear 5015**

PRODUCT RECOMMENDATION 3  
**Syngear TDL 75W-90**

Change every 40000 km/ 48 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1  
**SP Gear 1081**

Change every 40000 km/ 48 months

# NISSAN (EU) PATROL PATROL GR 2.8 TD

## 2WD Y60 (1988-1997)



### HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		
Change every 40000 km/ 48 months		

### POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		
Check every 20000 km/ 12 months		

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>
Change every 20000 km/ 12 months		

### COOLING SYSTEM

Capacity: 13,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	
Change every 40000 km/ 48 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.