

# NISSAN (EU) PRIMASTAR X83 PRIMASTAR 2.0 16V (2002-2007)



<b>ENGINE F4R</b> Capacity: 5,25 liter		
<b>USE</b> Normal		<b>CLIMATE</b> Mediterranean

<b>PRODUCT RECOMMENDATION 1</b> <b>Bi-Turbo 20W-50</b>		
---	--	--

*Change every 30000 km/ 24 months*

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Asyntho 5W-30</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Emperol 10W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Bi-Turbo 15W-40</b>
---	--	---

*Change every 30000 km/ 24 months*

<b>USE</b> Severe		<b>CLIMATE</b> Mediterranean
----------------------	--	---------------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Bi-Turbo 20W-50</b>		
---	--	--

*Change every 15000 km/ 12 months*

<b>USE</b> Severe		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Asyntho 5W-30</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Emperol 10W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Bi-Turbo 15W-40</b>
---	--	---

*Change every 15000 km/ 12 months*

<b>TRANSAXLE MANUAL PK6 6/1</b> Capacity: 2,7 liter		
--	--	--

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>SP Gear 5015</b>		
--	--	--

*Check every 60000 km*

<b>HYDRAULIC BRAKE/CLUTCH SYSTEM</b> Capacity: 0,7 liter		
---	--	--

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Drauliquid-LV Super DOT 4</b>		
---	--	--

*Check every 30000 km/ 24 months, change every 120000 km/ 48 months*

# NISSAN (EU) PRIMASTAR X83 PRIMASTAR 2.0 16V (2002-2007)



## POWER STEERING

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

Check every 24 months/ 30000 km

## COOLING SYSTEM

Capacity: 5,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Coolant SP 16</b>		

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*