## NISSAN (USA / CAN) NV200 COMPACT CARGO M20 NV200 TAXI 2.0 (USA) (2014-



2016)

ENGINE MR20DE Capacity: 4,4-5,1 liter (Service fill), Filter capacity: 0,3 liter				
	CLIMATE			
	Moderate			
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Presteza MSP 5W-30	Avanza RPC 5W-30			
	PRODUCT RECOMMENDATION 2			

Change every 3750 miles/3 months

TRANSMISSION CVT		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4016		
Charles a come 40000 miles / 40 magnifies about a come 20000 miles / 20 magnifies		

Check every 10000 miles/ 12 months, change every 30000 miles/ 36 months

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid DOT 3				
Change every 20000 miles/ 24 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid DOT 3				
Change every 10000 miles/ 12 months				

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

PRODUCT RECOMMENDATION

## NISSAN (USA / CAN) NV200 COMPACT CARGO M20 NV200 TAXI 2.0 (USA) (2014-



2016)

COOLING SYSTEM Capacity: 7,6 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Change every 75000 miles/ 60 months				
USE		CLIMATE		
First change only		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Change every 105000 miles/ 84 months				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.