PEUGEOT J5 J5 2.0 (1000, 1400, 1800) (1991-1994)



ENGINE Capacity: 4 liter, Filter capacity: 0,5 lite	re		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30	
Check every 3000 km, change every	10000 km/ 12 months		
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30	
Change every 5000 km/ 6 months			

CLIMATE	
CLIMATE	
Moderate	
	Moderate

Check every 10000 km, change every 40000 km

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 2500 km, change every 40000 km/24 months

POWER STEERING Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 20000 km	

PEUGEOT J5 J5 2.0 (1000, 1400, 1800) (1991-1994)



COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 2500 km, change every	/ 24 months	•

Check every 2500 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.