PEUGEOT J5 J5 2.5 TURBO D 4X4 (800, 1000, 1400, 1800) (1987-1991)



ENGINE CRD - U25/637 Capacity: 4,7 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

Change every 7500 km

DIFFERENTIAL REAR (4x4) Capacity: 1,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
<u></u>	

Check every 7500 km, change every 45000 km

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 SP Gear 5015	PRODUCT RECOMMENDATION 2 Gearlube RPC 75W-80	

Check every 7500 km, change every 45000 km

	Bradinquia e Berri		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
HYDRAULIC BRAKE SYSTEM			

Check every 2500 km, change every 45000 km

POWER STEERING Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 22500 km	

PEUGEOT J5 J5 2.5 TURBO D 4X4 (800, 1000, 1400, 1800) (1987-1991)



COOLING SYSTEM Capacity: 10,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 2500 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.