PIAGGIO PORTER MAXXI PORTER MAXXI 1.3 16V (2008 AND AFTER)



| ENGINE Capacity: 3,7 liter | | | |
|-------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Emperol 5W-40 | Asyntho 5W-30 | | |
| | · | · | |

Change every 10000 km/ 12 months

| DIFFERENTIAL REAR Capacity: 1,3 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 40000 km | , | |

| TRANSMISSION MANUAL 5/1 Capacity: 1,1 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |
| Change every 40000 km | 1 | ' |

| HYDRAULIC SYSTEM TIPPER Capacity: 4 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Perlus Biosynth 46 | Perlus H 46 | | |

| HYDRAULIC BRAKE SYSTEM | | |
|-----------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Check every 10000 km/12 months ch | ango over 24 months | |

Check every 10000 km/12 months, change every 24 months

PIAGGIO PORTER MAXXI PORTER MAXXI **1.3 16V** (2008 AND AFTER)



| COOLING SYSTEM Capacity: 5,7 liter | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |
| Check every 10000 km/ 12 months, change every 24 months | | |

Check every 10000 km/ 12 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.