## RAM TRUCKS (USA / CAN) RAM 2500/3500 DJ/D2/DD RAM 2500/3500 6.7 D (4X2) DJ



(2013-2014)

| <b>ENGINE</b> Cummins Capacity: 11,4 liter |                          |                          |
|--------------------------------------------|--------------------------|--------------------------|
| USE                                        |                          | CLIMATE                  |
| Flexible (max)                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Armado Synth LSP Ultra 10W-40              | Armado Synth MSP 5W-40   | Dieselfleet MSP 15W-40   |

Change every 15000 miles/ 6 months/ 500 hours

| DIFFERENTIAL REAR        |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| SP Gear 1071             |          |
| Check every 20000 miles  |          |
| USE                      | CLIMATE  |
| Severe                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| SP Gear 1071             |          |
| Change every 20000 miles |          |

| DIFFERENTIAL REAR LIMITED SLIP |          |
|--------------------------------|----------|
| USE                            | CLIMATE  |
| Normal                         | Moderate |
| PRODUCT RECOMMENDATION 1       |          |
| SP Gear 1071                   |          |
| Check every 20000 miles        |          |
| USE                            | CLIMATE  |
| Severe                         | Moderate |
| PRODUCT RECOMMENDATION 1       |          |
| SP Gear 1071                   |          |
| Change every 20000 miles       |          |
|                                |          |

## RAM TRUCKS (USA / CAN) RAM 2500/3500 DJ/D2/DD RAM 2500/3500 6.7 D (4X2) DJ



(2013-2014)

| (2013 2014)                                                                       |   |          |
|-----------------------------------------------------------------------------------|---|----------|
| <b>TRANSMISSION AUTOMATIC</b> 68RFE 6/<br>Capacity: 5,2 liter (Service fill)      | 1 |          |
| USE                                                                               |   | CLIMATE  |
| Normal                                                                            |   | Moderate |
| PRODUCT RECOMMENDATION 1                                                          |   |          |
| SP Matic 4026                                                                     |   |          |
| Change every 120000 miles/ 96 months                                              |   |          |
| USE                                                                               |   | CLIMATE  |
| Severe                                                                            |   | Moderate |
| PRODUCT RECOMMENDATION 1                                                          |   |          |
| SP Matic 4026                                                                     |   |          |
| Change every 60000 miles/ 48 months                                               |   |          |
|                                                                                   |   |          |
| TRANSMISSION AUTOMATIC Aisin War Capacity: 13 liter (Dry fill), Capacity: 6,8 lit |   |          |
| USE                                                                               |   | CLIMATE  |
| Normal                                                                            |   | Moderate |
| PRODUCT RECOMMENDATION 1                                                          |   |          |
| SP Matic 4026                                                                     |   |          |
| Change every 30000 miles/ 24 months                                               |   |          |
|                                                                                   |   |          |
| TRANSMISSION MANUAL G56 6/1 Capacity: 4,7 liter                                   |   |          |
| USE                                                                               |   | CLIMATE  |
| Severe                                                                            |   | Moderate |
| PRODUCT RECOMMENDATION 1                                                          |   |          |
| SP Matic 4026                                                                     |   |          |
| Change every 60000 miles/ 48 months                                               |   |          |
|                                                                                   |   |          |
| HYDRAULIC BRAKE SYSTEM                                                            |   |          |
| USE                                                                               |   | CLIMATE  |
| Normal                                                                            |   | Moderate |
| PRODUCT RECOMMENDATION 1                                                          |   |          |
| Drauliquid DOT 3                                                                  |   |          |

PRODUCT RECOMMENDATION

## RAM TRUCKS (USA / CAN) RAM 2500/3500 DJ/D2/DD RAM 2500/3500 6.7 D (4X2) DJ



(2013-2014)

| HYDRAULIC CLUTCH SYSTEM  |  |          |  |
|--------------------------|--|----------|--|
| USE                      |  | CLIMATE  |  |
| Normal                   |  | Moderate |  |
| PRODUCT RECOMMENDATION 1 |  |          |  |
| Drauliquid DOT 3         |  |          |  |

| POWER STEERING                      |          |
|-------------------------------------|----------|
| USE                                 | CLIMATE  |
| Normal                              | Moderate |
| PRODUCT RECOMMENDATION 1            |          |
| SP Matic 4026                       |          |
| Change every 97500 miles/ 78 months | '        |

| COOLING SYSTEM<br>Capacity: 21,4 liter |                          |          |  |
|----------------------------------------|--------------------------|----------|--|
| USE                                    |                          | CLIMATE  |  |
| Normal                                 |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 |          |  |
| Coolant SP 15+                         | Coolant SP 12            |          |  |
| 0/ 450000 1/ /400                      | 4                        |          |  |

Change every 150000 miles/ 120 months

## **DIESEL EXHAUST FLUID**

Capacity: 21 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.