## DODGE RAM (USA / CAN) RAM CHASSIS CAB DR/DH/D1/DC/DM RAM CHASSIS CAB 4500/5500 6.7 D (4X2) DR/DH/D1/DC/DM



ENGINE Summins Capacity: 11,4 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Dieselfleet MSP 15W-40				
Change every 12000 km/ 6 months				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40			

DIFFERENTIAL REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change every 24000 km/ 12 month	ns	1

DIFFERENTIAL REAR LIMITED SLIP				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90		
Changes are at 24000 lene/40 magnifica				

Change every 24000 km/ 12 months

Change every 12000 km/6 months

TRANSMISSION AUTOMATIC Aisin Warner AS68RC 6/1			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Change every 48000 km/ 24 months			

PRODUCT RECOMMENDATION

## DODGE RAM (USA / CAN) RAM CHASSIS CAB DR/DH/D1/DC/DM RAM CHASSIS CAB 4500/5500 6.7 D (4X2) DR/DH/D1/DC/DM



	,	
TEANSMISSION MANUAL G56 6/1		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 97000 km/ 48 months		
HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
		Moderate
PRODUCT RECOMMENDATION 1  Drauliquid DOT 3		
POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 156000 km/ 78 months		
COOLING SYSTEM		
Capacity: 21,4 liter		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

USE

Normal

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

Change every 160000 km/60 months

CLIMATE

Moderate