

# RENAULT (EU) MASCOTT MASCOTT 150 DXI EURO 4/5 (2007-2010)



**ENGINE** ZDK A608  
Capacity: 10,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 60000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 40000 km/ 24 months*

**DIFFERENTIAL REAR** M248 / M273  
Capacity: 3,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 400000 km/ 36 months*

**DIFFERENTIAL REAR** P 569  
Capacity: 4,2 liter, Capacity: 0,15 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 120000 km/ 24 months*

**DIFFERENTIAL REAR** P 669  
Capacity: 5,5 liter, Capacity: 0,15 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 240000 km/ 24 months*

**POWER TAKE OFF**  
Capacity: 0,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

# RENAULT (EU) MASCOTT MASCOTT 150 DXI EURO 4/5 (2007-2010)



**TRANSMISSION MANUAL** ZF 6S-380 6/1  
Capacity: 2,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRANSMISSION MANUAL** ZF S6-350 DD 6/1  
Capacity: 2,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## HYDRAULIC BRAKE SYSTEM ABS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

## COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 16</b>		

*Change every 400000 km/ 36 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*