RENAULT (EU) MASTER II X70 MASTER II 3.0 DCI (2004-2007)



| ENGINE ZD3 Capacity: 7,3 liter, Filter capacity: 0,5 liter | | | | |
|--|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Helar 0W-40 | Emperol 5W-40 | Asyntho 5W-30 | | |
| Change every 40000 km/ 24 months | | | | |
| USE | | CLIMATE | | |
| Severe | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Helar 0W-40 | Emperol 5W-40 | Asyntho 5W-30 | | |
| Change every 10000 km/ 6 months | | | | |

| OL IMATE |
|----------|
| CLIMATE |
| Moderate |
| |
| |
| |

| HYDRAULIC BRAKE SYSTEM ABS AS OPTION Capacity: 0,7 liter, Capacity: 1 liter (ABS) | | | | |
|---|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | | |

Check every 40000 km/24 months, change every 120000 km/48 months

| POWER STEERING Capacity: 1,1 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF Dexron II-D | |
| Check every 40000 km/ 24 months | |

RENAULT (EU) MASTER II X70 MASTER II 3.0 DCI (2004-2007)



| COOLING SYSTEM Capacity: 10,5 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 16 | | |
| Chack every 40000 km/24 months, change every 120000 km/48 months | | |

Check every 40000 km/ 24 months, change every 120000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.