

RENAULT (EU) MASTER III X62 MASTER III

2.3 DCI 125 RWD X62 (2010-2016)



ENGINE M9T
Capacity: 8,9 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40

PRODUCT RECOMMENDATION 2

Helar 0W-40

PRODUCT RECOMMENDATION 3

Emperol 5W-40

Change every 40000 km/ 24 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40

PRODUCT RECOMMENDATION 2

Helar 0W-40

PRODUCT RECOMMENDATION 3

Emperol 5W-40

Change every 20000 km/ 12 months

DIFFERENTIAL REAR (4x2)
Capacity: 2,7-3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

TRANSAXLE MANUAL ZF4 6/1
Capacity: 2,2 liter, Capacity: 2,4 liter (+ PTO)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Syngear MT/LD 75W-80

TRANSAXLE SEMI-AUTOMATIC ZA4 6/1
Capacity: 2,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

RENAULT (EU) MASTER III X62 MASTER III

2.3 DCI 125 RWD X62 (2010-2016)



HYDRAULIC GEARBOX ACTUATION SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 120000 km/ 48 months

ELECTRO-HYDRAULIC POWER STEERING

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		

Change every 160000 km/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.