## RENAULT (EU) MAXITY MAXITY 150 DXI



(2008-2014)

<b>ENGINE</b> DXi 3 (ZD3 A600) Capacity: 9,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Synfleet SHPD 10W-40	
Change every 30000 km/ 12 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Synfleet SHPD 10W-40	
Change every 15000 km/ 12 months	

<b>DIFFERENTIAL REAR</b> H260 Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 60000 km/24 months		

	<u> </u>	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Severe		Moderate
USE		CLIMATE

Change every 30000 km/24 months

**DIFFERENTIAL REAR** H290

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Unigear HS GL-3/GL-5 80W-90	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Unigear HS GL-3/GL-5 80W-90	
	Unigear HS GL-3/GL-5 80W-90  PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION

## **RENAULT (EU) MAXITY MAXITY 150 DXI**

(2008-2014)



## **POWER TAKE OFF**

Capacity: 0,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## TRANSMISSION MANUAL ZF 6S-380 6/1

Capacity: 2,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

COOLING SYSTEM Capacity: 12,5 liter, Capacity: 13,2 liter (+ rear heater)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 16			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.