

RENAULT (EU) TRAFIC TRAFIC T 800D, T 1000D, T 1200D 2.1 4X4 (1986-1989)

**ENGINE 852/J8S**

Capacity: 5 liter, Filter capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Bi-Turbo 15W-40	Synfleet SHPD 10W-40

*Change every 7500 km***DIFFERENTIAL FRONT (4x2)**

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Check every 7500 km, change every 60000 km

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

*Check every 7500 km, change every 60000 km***DIFFERENTIAL REAR (4x4)**

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 7500 km, change every 60000 km

RENAULT (EU) TRAFIC TRAFIC T 800D, T 1000D, T 1200D 2.1 4X4 (1986-1989)



TRANSMISSION MANUAL S5-24 5/1

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Check every 7500 km, change every 60000 km

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Check every 7500 km, change every 60000 km

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 60000 km

COOLING SYSTEM

Capacity: 8,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.