

TOYOTA (EU) HI-ACE HI-ACE 2.7I (2012-2015)

**ENGINE 2TR-FE**

Capacity: 5,5 liter, Filter capacity: 0,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Check every 3000 km, change every 10000 km/ 12 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Asyntho 5W-30****PRODUCT RECOMMENDATION 3****Emperol 10W-40***Check every 3000 km, change every 10000 km/ 12 months***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Xedoz FE 5W-30***Check every 3000 km, change every 10000 km/ 12 months***USE**

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Change every 5000 km/ 6 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Asyntho 5W-30****PRODUCT RECOMMENDATION 3****Emperol 10W-40***Change every 5000 km/ 6 months***USE**

Severe

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Xedoz FE 5W-30***Change every 5000 km/ 6 months*

TOYOTA (EU) HI-ACE HI-ACE 2.7i (2012-2015)



DIFFERENTIAL REAR

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 30000 km/ 48 months

| USE | | CLIMATE |
|--------------------------|----------------------------|--------------------------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 5015 | Gearlube RPC 75W-80 | SP Gear 1071 |

Change every 30000 km/ 48 months

TRANSAXLE AUTOMATIC 5/1

Capacity: 8,3 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |

Change every 90000 km/ 72 months

| USE | | CLIMATE |
|--------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |

Change every 45000 km/ 36 months

TRANSMISSION MANUAL 5/1

Capacity: 2,6 liter

| USE | | CLIMATE |
|--------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

Change every 48 months

| USE | | CLIMATE |
|--------------------------|---------------------------|--------------------------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

Change every 60000 km/ 48 months

TOYOTA (EU) HI-ACE HI-ACE 2.7I (2012-2015)



HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |
| <i>Change every 30000 km/ 24 months</i> | | |

HYDRAULIC CLUTCH SYSTEM

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |
| <i>Change every 24 months</i> | | |

POWER STEERING

Capacity: 0,9 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |
| <i>Change every 24 months</i> | | |

COOLING SYSTEM

Capacity: 15 liter, Capacity: 17 liter (with 4 zone airconditioning system)

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |
| <i>Change every 90000 km</i> | | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |
| <i>Change every 150000 km</i> | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.