

TOYOTA (EU) HILUX AN10 / AN20 HILUX 2.7

VVT-I 2WD (2005-2008)

**ENGINE** 2TR-FE

Capacity: 6,3 liter (Dry fill), Capacity: 5,6 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Emperol 10W-40*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Emperol 10W-40*Change every 7500 km/ 6 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 7500 km/ 6 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Emperol 10W-40*Change every 7500 km/ 6 months*

TOYOTA (EU) HILUX AN10 / AN20 HILUX 2.7 VVT-I 2WD (2005-2008)



DIFFERENTIAL REAR

Capacity: 2,3-3,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 30000 km/ 48 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Change every 30000 km/ 48 months

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 2,3-3,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 30000 km/ 48 months

DIFFERENTIAL REAR WITH DIFFERENTIAL LOCK

Capacity: 2,85-2,95 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 30000 km/ 48 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Change every 30000 km/ 48 months

TOYOTA (EU) HILUX AN10 / AN20 HILUX 2.7 VVT-I 2WD (2005-2008)



TRANSMISSION MANUAL R150 5/1

Capacity: 2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Check every 45000 km/ 48 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Change every 45000 km/ 48 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 30000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 24 months/ 30000 km

POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 24 months/ 30000 km

TOYOTA (EU) HILUX AN10 / AN20 HILUX 2.7 VVT-I 2WD (2005-2008)



COOLING SYSTEM

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 15000 km/ 12 months, change every 90000 km/ 72 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 15000 km/ 12 months, change every 150000 km/ 120 months

AIRCONDITIONING COMPRESSOR R-134a

Capacity: 195 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 420-480 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.