

# TOYOTA (EU) HILUX AN10 / AN20 HILUX 3.0 D 2WD (2006-2011)

**ENGINE 5L-E**

Capacity: 7,2 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Bi-Turbo 15W-40</b>	<b>Bi-Turbo 20W-50</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>	<b>Armado Synth 5W-30</b>

*Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Bi-Turbo 15W-40</b>	<b>Bi-Turbo 20W-50</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>	<b>Armado Synth 5W-30</b>

*Change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 7500 km/ 6 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Bi-Turbo 15W-40</b>	<b>Bi-Turbo 20W-50</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 7500 km/ 6 months*

# TOYOTA (EU) HILUX AN10 / AN20 HILUX 3.0 D 2WD (2006-2011)



USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Asyntho 5W-30</b>	<b>Armado Synth 5W-30</b>

*Change every 7500 km/ 6 months*

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 7500 km/ 6 months*

DIFFERENTIAL REAR		
Capacity: 2,3-3,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 30000 km/ 48 months*

DIFFERENTIAL REAR LIMITED SLIP		
Capacity: 3,15-3,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 30000 km/ 48 months*

TRANSMISSION MANUAL 5/1		
Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Syngear 75W-90</b>

*Change every 48 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Syngear 75W-90</b>

*Change every 45000 km/ 48 months*

# TOYOTA (EU) HILUX AN10 / AN20 HILUX 3.0 D 2WD (2006-2011)



## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		
<i>Change every 30000 km/ 24 months</i>		

## HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		
<i>Check every 24 months/ 30000 km</i>		

## POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>
<i>Change every 24 months</i>		

## COOLING SYSTEM

Capacity: 9,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		
<i>Check every 15000 km/ 12 months, change every 90000 km/ 72 months</i>		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		
<i>Check every 15000 km/ 12 months, change every 150000 km/ 120 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.