

# VAUXHALL COMBO C COMBO C 1.6 (2004-2005)

**ENGINE Z16SE**

Capacity: 3,5 liter, Filter capacity: 0,25 liter

USE		CLIMATE
ECOService-Flex (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 5W-30</b>	<b>Specialsynth MSP 5W-40</b>	<b>Helar 0W-40</b>

*Change every 30000 km/ 24 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>SP Gear 5015</b>	<b>Syngear TDL 75W-90</b>

*Check every 24 months/ 30000 km***HYDRAULIC BRAKE SYSTEM ABS AS OPTION**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 30000 km, change every 24 months***COOLING SYSTEM**

Capacity: 5,9 liter, Capacity: 6,2 liter (+ airconditioning)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	

*Check every 24 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.