

VAUXHALL MOVANO B X62 MOVANO B 2.3 CDTI (81 KW) FWD DPF (2014-2016)



ENGINE M9T 870
Capacity: 8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|---------------------------|
| Helar SP LL-03 5W-30 | Presteza MSP 5W-30 |

Change every 40000 km/ 24 months

TRANSAXLE MANUAL PF6 6/1
Capacity: 2,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Gear 5015 | |

TRANSAXLE SEMI-AUTOMATIC PA0 6/1
Capacity: 5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Gear 5015 | |

HYDRAULIC BRAKE SYSTEM
Capacity: 1,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|----------------------------------|---------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 |

Change every 120000 km/ 48 months

HYDRAULIC CLUTCH SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|----------------------------------|---------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 |

Change every 120000 km/ 48 months

VAUXHALL MOVANO B X62 MOVANO B 2.3 CDTI (81 KW) FWD DPF (2014-2016)



POWER STEERING

Capacity: 2,5 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4036 | | |

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15 | Coolant SP 15+ | |

Change every 160000 km/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.