

VOLKSWAGEN (VW) (EU) CADDY SA

CADDY 1.4 TSI (92 KW) (2015-2020)



ENGINE CZCA, CZCB
Capacity: 4 liter (Service fill)

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Change every 30000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 02S 6/1
Capacity: 2,1-2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

TRANSAXLE SEMI-AUTOMATIC DSG 0AM (DQ200) 7/1
Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

Change every 60000 km

HYDRAULIC ACTUATION GEARBOX
Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

VOLKSWAGEN (VW) (EU) CADDY SA

CADDY 1.4 TSI (92 KW) (2015-2020)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 1,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

COOLING SYSTEM AS OF PRODUCTION DATE 25-11-2019

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Check every 60000 km/ 4 months*

COOLING SYSTEM UP TO PRODUCTION DATE 25-11-2019

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Check every 48 months/ 60000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.