VOLKSWAGEN (VW) (EU) TRANSPORTER III TRANSPORTER/CARAVELLE 1.6 TD (51



KW) (1985-1990)

| ENGINE JX Capacity: 4,5 liter, Filter capacity: 0,5 liter | | | |
|---|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | | | |
| Bi-Turbo 20W-50 | | | |
| Change every 7500 km/ 12 months | | | |
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Emperol 10W-40 | Bi-Turbo 15W-40 | Multifleet SHPD 15W-40 | |
| Change every 7500 km/ 12 months | | | |

| TRANSAXLE MANUAL 4/1 | | | | |
|--------------------------|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| SP Gear 5015 | Gearlube GL-4 80W | Gearlube GL-4 80W-90 | | |

| SP Gear 5015 | Gearlube GL-4 80W | Gearlube GL-4 80W-90 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |
| TRANSAXLE MANUAL 5/1 | | |

| HYDRAULIC BRAKE SYSTEM | | | |
|---------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| Change every 24 months | ' | ' | |

Dollegoorweg 15

7602 EC Almelo

PRODUCT RECOMMENDATION

VOLKSWAGEN (VW) (EU) TRANSPORTER III TRANSPORTER/CARAVELLE 1.6 TD (51 KW) (1985-1990)



| COOLING SYSTEM Capacity: 16 liter | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 11 | |
| Change every 24 months | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.