

CHEVROLET (USA / CAN) SILVERADO

GMT901 SILVERADO HYBRID (2009-2010)



MOTOR LFA
Kapacitet: 5,7 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Xedoz FE 5W-30

Skift alle 12 måneder

DIFFERENTIALE BAG
Kapacitet: 2,03-2,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

GEAR AUTOMATISK 4/1
Kapacitet: 4,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 12 måneder, skift alle 100000 mil

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 12 måneder, skift alle 50000 mil

HYDRAULISK BREMSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

CHEVROLET (USA / CAN) SILVERADO GMT901 SILVERADO HYBRID (2009-2010)



SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 2032		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

KØLESYSTEM MOTOR

Kapacitet: 16,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15	Coolant SP 15+	

Kontroller alle 12 måneder, skift alle 150000 mil/ 60 måneder

KØLESYSTEM STRØMELEKTRONIK

Kapacitet: 2,7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15	Coolant SP 15+	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.