

CITROËN BERLINGO B9 BERLINGO 1.6I VTI 5FS (2009-2012)



MOTOR EP6

Kapacitet: 4,25 liter, Filterkapacitet: 0,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30

Skift alle 30000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30

Skift alle 20000 km/ 12 måneder

TRANSAKSEL MANUEL MA 5/1

Kapacitet: 1,8 liter

ANVEND	KLIMA
Fyldt på livstid	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 24 måneder/ 30000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Kontroller alle 20000 km/ 12 måneder, skift alle 60000 km/ 24 måneder

ELEKTRISK-HYDRAULISK SERVOSTYRING (EHPS)

Kapacitet: 1,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 24 måneder/ 30000 km

CITROËN BERLINGO B9 BERLINGO 1.6I VTI 5FS (2009-2012)



HYDRAULISK SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

KØLESYSTEM

Kapacitet: 5,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 20000 km/ 12 måneder, skift alle 120000 km/ 60 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 135 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.