

# CITROËN C15 C 15E 1,3 (G-MOTOR) (1987-1988)



## MOTOR G1A

Kapacitet: 3,5 liter, Filterkapacitet: 0,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3  |
|-------------------------------|----------------------|----------------------|
| <b>Specialsynth MSP 5W-40</b> | <b>Emperol 5W-40</b> | <b>Asyntho 5W-30</b> |

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3  |
|-------------------------------|----------------------|----------------------|
| <b>Specialsynth MSP 5W-40</b> | <b>Emperol 5W-40</b> | <b>Asyntho 5W-30</b> |

Skift alle 7500 km/ 12 måneder

## TRANSAXSEL MANUEL 4/1

Kapacitet: 2 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2        |  |
|---------------------|----------------------------|--|
| <b>SP Gear 5015</b> | <b>Gearlube RPC 75W-80</b> |  |

Kontroller alle 10000 km, skift alle 40000 km

## HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |  |
|----------------------------------|---------------------------|--|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |  |

Kontroller alle 1000 km, skift alle 60000 km/ 24 måneder

## KØLESYSTEM

Kapacitet: 6,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |  |
|-------------------------------|---------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |  |

Kontroller alle 1000 km, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.