

CITROËN C25 C 25 D 2.0 4X4 (1989-1990)



MOTOR D 9B/XUD 9A

Kapacitet: 5 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 15W-40	Multifleet SHPD 15W-40	

Skift alle 7500 km/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Skift alle 7500 km/ 12 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 15W-40	Multifleet SHPD 15W-40	

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Skift alle 5000 km/ 6 måneder

DIFFERENTIALE BAG (4x4)

Kapacitet: 1,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 7500 km, skift alle 22500 km

TRANSAKSEL MANUEL 4/1

Kapacitet: 2,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 7500 km, skift alle 22500 km

CITROËN C25 C 25 D 2.0 4X4 (1989-1990)



HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 1000 km, skift alle 67500 km/ 24 måneder

SERVOSTYRING

Kapacitet: 1,4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 22500 km

KØLESYSTEM

Kapacitet: 9,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 1000 km, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.