

CITROËN JUMPER / RELAY JUMPER / RELAY 2.0i (2000-2002)



MOTOR XU10J2U

Kapacitet: 5 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Avanza MSP 0W-30

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Avanza MSP+ 5W-30

Skift alle 20000 km/ 12 måneder

TRANSAKSEL MANUEL ME5TU 5/1

Kapacitet: 1,85 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

Kontroller alle 60000 km

TRANSAKSEL MANUEL MG5TU 5/1

Kapacitet: 2,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

Kontroller alle 60000 km

TRANSAKSEL MANUEL MLGU5 5/1

Kapacitet: 2,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

Kontroller alle 60000 km

TRANSAKSEL MANUEL MLUC 5/1

Kapacitet: 2,1 liter (Servicepåfyldning), Kapacitet: 2,4 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 60000 km

CITROËN JUMPER / RELAY JUMPER / RELAY 2.0i (2000-2002)



HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 60000 km/ 24 måneder

SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 20000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 9,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 20000 km/ 12 måneder, skift alle 120000 km/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.