

CITROËN JUMPER / RELAY JUMPER / RELAY 2.5 D (1999-2002)



MOTOR T9A (DJ5)

Kapacitet: 9 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL ME5TU 5/1

Kapacitet: 1,85 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 60000 km

TRANSAKSEL MANUEL MG5TU 5/1

Kapacitet: 2,75 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 60000 km

TRANSAKSEL MANUEL MLGU5 5/1

Kapacitet: 2,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 60000 km

TRANSAKSEL MANUEL MLUC 5/1

Kapacitet: 2,1 liter (Servicepåfyldning), Kapacitet: 2,4 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 60000 km

CITROËN JUMPER / RELAY JUMPER / RELAY 2.5 D (1999-2002)



HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
<i>Skift alle 60000 km/ 24 måneder</i>		

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		
<i>Kontroller alle 15000 km/ 12 måneder</i>		

KØLESYSTEM

Kapacitet: 13 liter, Kapacitet: 13,5 liter (+ klimaanlæg)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	
<i>Kontroller alle 15000 km/ 12 måneder, skift alle 120000 km/ 60 måneder</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.