

FIAT (EU) DUCATO 250, 290 DUCATO 3.0 MULTIJET 160 EURO 5 (2010-2011)



MOTOR F1CE3481 M
Kapacitet: 9 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Skift alle 40000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Skift alle 20000 km/ 12 måneder

HYDRAULISK AKTIVERING GEARCASE
Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3023		

TRANSAKSEL HALVAUTOMATISK M38, M40 6/1
Kapacitet: 2,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

TRANSAKSEL MANUEL M38, M40 6/1
Kapacitet: 2,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

FIAT (EU) DUCATO 250, 290 DUCATO 3.0 MULTIJET 160 EURO 5 (2010-2011)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 90000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Kontroller alle 90000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 11-11,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 40000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.