

FIAT (EU) DUCATO 250, 290 DUCATO 3.0 MULTIJET 160 (2006-2010)



MOTOR F1CE0481 D

Kapacitet: 7 liter (Servicepåfyldning), Filterkapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

Skift alle 40000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

Skift alle 20000 km/ 12 måneder

HYDRAULISK AKTIVERING GEARKASSE

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Fluid 3023

TRANSAKSEL HALVAUTOMATISK M38, M40 6/1

Kapacitet: 2,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear MT/LD 75W-80

PRODUKTANBEFALING 3

Syngear 75W-90

TRANSAKSEL MANUEL M38, M40 6/1

Kapacitet: 2,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear MT/LD 75W-80

PRODUKTANBEFALING 3

Syngear 75W-90

FIAT (EU) DUCATO 250, 290 DUCATO 3.0 MULTIJET 160 (2006-2010)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Skift alle 90000 km/ 24 måneder*

SERVOSTYRING

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032*Kontroller alle 90000 km/ 12 måneder*

SMØREPUNKTER/NIPLER HOMOKINETISKE LED DIFFERENTIALESIDE

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER HOMOKINETISKE LED HJULSIDE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 11-11,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+*Kontroller alle 40000 km/ 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.