

FORD (EU) TRANSIT V184/V185 TRANSIT 1.6 (1986-1988)



MOTOR OHC, L..

Kapacitet: 3,75 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Bi-Turbo 15W-40

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Asyntho 5W-30

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

Kontroller alle 20000 km/ 12 måneder

GEAR MANUEL F 4/1

Kapacitet: 1,45 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Kontroller alle 20000 km/ 12 måneder

FORD (EU) TRANSIT V184/V185 TRANSIT 1.6 (1986-1988)



GEAR MANUEL G 4/1

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Kontroller alle 20000 km/ 12 måneder

GEAR MANUEL MT75 5/1

Kapacitet: 1,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Kontroller alle 20000 km/ 12 måneder

GEAR MANUEL N 5/1

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Syngear 75W-90

PRODUKTANBEFALING 2

Gearlube GL-4 80W-90

Kontroller alle 20000 km/ 12 måneder

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 60000 km/ 36 måneder

SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4016

PRODUKTANBEFALING 2

ATF Dexron II-D

FORD (EU) TRANSIT V184/V185 TRANSIT 1.6 (1986-1988)



KØLESYSTEM

Kapacitet: 7,2 liter, Kapacitet: 8,4 liter (+ varmeapparat)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

PRODUKTANBEFALING 2

Coolant -38 Organic NF

PRODUKTANBEFALING 3

Coolant -26

Skift alle 60000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.