

FORD (EU) TRANSIT V184/V185 TRANSIT 2.0 (1986-1988)

**ENGINE N..**

Capacity: 3,75 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Check every 3000 km, change every 10000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 20000 km/ 12 months***TRANSMISSION AUTOMATIC C3 3/1**

Capacity: 6,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4016

PRODUCT RECOMMENDATION 2

ATF Dexron II-D*Check every 20000 km/ 12 months*

FORD (EU) TRANSIT V184/V185 TRANSIT 2.0 (1986-1988)


TRANSMISSION MANUAL F 5/1

Capacity: 1,45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Check every 20000 km/ 12 months

TRANSMISSION MANUAL G 5/1

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Check every 20000 km/ 12 months

TRANSMISSION MANUAL N 5/1

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Syngear 75W-90	Gearlube GL-4 80W-90	

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 60000 km/ 36 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4016	ATF Dexron II-D	

FORD (EU) TRANSIT V184/V185 TRANSIT 2.0 (1986-1988)

**COOLING SYSTEM**

Capacity: 8,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 11	Coolant -38 Organic NF	Coolant -26

Change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.