

FORD (EU) TRANSIT V184/V185 TRANSIT 2.5 DI (1995-1998)



MOTOR 4G

Kapacitet: 6 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 20W-50	Multifleet SHPD 20W-50	

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza LSP 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 1,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		

Kontroller alle 20000 km/ 12 måneder

GEAR AUTOMATISK AL4D 4/1

Kapacitet: 8,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 4016	ATF Dexron II-D	

Kontroller alle 20000 km/ 12 måneder

GEAR MANUEL MT75 5/1

Kapacitet: 1,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 20000 km/ 12 måneder

FORD (EU) TRANSIT V184/V185 TRANSIT 2.5 DI (1995-1998)



HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 60000 km/ 36 måneder

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 4016	ATF Dexron II-D	

KØLESYSTEM

Kapacitet: 11,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 11	Coolant -38 Organic NF	Coolant -26

Skift alle 60000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.